

Product sheet

# Mesh

## armchair

### Technical Data

- Shield - mesh (Runner), frame Ø25 mm, upholstered, two fabric layers attached to the frame with zip: M - small shield, S - medium shield, D - large shield;
- Seat, backrest, armrests - moulded foam, upholstered;
- Base - 4-legged, metal, powder coated, Ø25 mm, wall thickness 1,5 mm, CNC-bent, legs finished with polypropylene feet, colour: white - white frame; colour: black - other frame colours

### Selected configuration

#### MF1D

**Height:** 1210 mm

**Width:** 810 mm

**Length:** 1000 mm

**Colour of the seat:** M-63017 Rusty

**Colour of the shield:** M-61189 Beige

**Colour of the base:** Beige semi-matte RAL 0608005

### Sustainability

- Sustainable production – we are not indifferent to the environmental impact of our furniture, therefore we provide the essential information on the life cycle of Mesh seating through the Environmental Product Declaration (EPD).
- Steel profiles are powder-coated to reduce the emission of Volatile Organic Compounds.
- Sustainable production – we are not indifferent to the environmental impact of our furniture, therefore we provide the essential information on the life cycle of our products through the Environmental Product Declarations (EPD).

### Material composition



### Guarantee

.mdd products - 5 years.

Electrical components - 2 years.

### Assembly manuals

Pre-assembled product. Product does not require assembly.

### Certificates



- MFC: 6%
- Steel: 46%
- Plastic: 10%
- Fabric: 6%
- Cardboard: 15%
- Polyurethane foam: 17%

\*average values for a representative of the group.

---

## Recycled content

34%

---

## Recyclability

- Recyclable: 100%
- Downcyclable: 0%

\*average values for a representative of the group.

---

## Fabric technical data

### M-63017 Rusty



<b>Material</b>	100% polyester
<b>Weight</b>	364g/m <sup>2</sup> · 510g/lm
<b>Abrasion resistance rubs</b>	75,000 Martindale cycles
<b>Pilling resistance</b>	scale 1-5, max 5 · EN ISO 12945-2 4
<b>Colour fastness to light</b>	scale 1-8, max 8 · EN ISO 105 - B02 5-7
<b>Colour fastness to rubbing</b>	scale 1-5, max 5 · EN ISO 105x12 (wet/dry) 4-5/4-5
<b>Acoustic test sound absorption</b>	ISO 354
<b>Flammability</b>	BS EN 1021 - 1:2006 (cigarette), BS EN 1021 - 2:2006 California Bulletin CAL 117-E-Class 1

**M-61189 Beige**



<b>Material</b>	100% polyester
<b>Weight</b>	364g/m2 • 510g/lm
<b>Abrasion resistance rubs</b>	75,000 Martindale cycles
<b>Pilling resistance</b>	scale 1-5, max 5 • EN ISO 12945-2 4
<b>Colour fastness to light</b>	scale 1-8, max 8 • EN ISO 105 - B02 5-7
<b>Colour fastness to rubbing</b>	scale 1-5, max 5 • EN ISO 105x12 (wet/dry) 4-5/4-5
<b>Acoustic test sound absorption</b>	ISO 354
<b>Flammability</b>	BS EN 1021 - 1:2006 (cigarette), BS EN 1021 - 2:2006 California Bulletin CAL 117-E-Class 1