

DATASHEET

# PLANET LED PUCK

AIR CATENARY

Compact Catenary System

### Minimal Footprint Maximum Effect

LED Puck Air is the incredibly lightweight, highly versatile, and exceptionally elegant catenary lighting system for today's modern world. High performance yet only a fraction of the size and weight of other systems, Air enables safe, reliable, clutter-free catenary and welcomes infinite design possibilities for everything from outdoor gathering spaces to indoor accent lighting.



### **AIR CATENARY**

Planet LED Puck Air Catenary gives designers and engineers unparalleled aesthetic discretion and precise lighting control in a lightweight, and endlessly versatile catenary package.

With a luminaire weighing in at only 100g, Air's clever, clutter-free system maximises design options and the potential of urban and public lighting.

Discover limitless applications across indoor and outdoor applications including highend retail, captivating displays, immersive galleries, and extraordinary outdoor spaces.

#### SPECIFICATIONS\*











ETLus conforms to UL2108 cETL conforms to CSA C22.2 #250.0





Engineer the experience with Air Catenary.







CREE 🔷











### **Protection Class**

IP67 / IK10

#### Electrical

24VDC

#### Installation

Ø3mm twin cable suspension (supplied by manufacturer)

#### Control

GLOBAL: O-10, DMX, RDM, DALI, Phase, INDIVIDUAL: DMX, RDM, DALI, Casambi

#### Dimensions & Weight

Ø25mm x Ø150mm (standard body) ~100g per luminaire (standard body) See following pages.

#### **Cable Specifications**

Single core 1.00mm<sup>2</sup> tinned copper with Kevlar braid

#### **Technical**

3 Step MacAdam Ellipse L90 B10 >100,000h CRI 80+ (CRI 90+ option)

#### Performance

Up to 850lm (8W @ 4000k over 100lm/w)

#### **Optics**

Polycarbonate / PMMA

#### Distribution

Available in a range of distributions: Circular, Oval, Decorative (see pages 4-6)

#### **Emitter Options**

BINNING: 3-step bins, 2200K-5700K CCT Tunable White, RGBW and 17 colour options

#### Material

Marine Grade Aluminium

Anodised Black Matte (Standard) Lens Ring Colour Options Available

#### **Ambient Operating Conditions**

Min. -40°C / Max. 55°C

\*Specifications are subject to change without notice










#### **BODY OPTIONS**

Get creative with Planet LED Puck Air's clever family of options.

Choose either Standard, Axis or Pendant body type, then select your distribution, emitter and options. Interchangeable accessories and options are also available.

**Axis** 

Note, final dimensions will depend on which options are chosen.











weight ~145g + 15g cable length per 5

- Ø25

Not to scale Dimensions in mm

#### **PHOTOMETRICS**


Available in a range of distribution options from our Air family.





#### **Air Director**

Precise, high uniformity and limitless flexibility, our Air Director series lets you sculpt with light with incredible control.

#### **Air Spots**











Air Floods

Snoot




#### **Air Batwings**



# New Asymmetric Range: Air Street!

Our new asymmetric options are optimised for road and path lighting. Air Street enables extremely wide spacings while maintaining great uniformity and light levels.

#### **Air Street**









#### **PHOTOMETRICS**

Available in a range of distribution options from our Air family.




#### **Air Director**

Precise, high uniformity and limitless flexibility, our Air Director series lets you sculpt with light with incredible control.



#### Air Zoom

Flexible focus beam adjustment from narrow to wide (~10° to 60°)





#### Air Iris

Adjustable beam limiter from narrow to wide



Special beams Air Zoom (top right) and Air Iris (bottom right)









#### **PHOTOMETRICS**



#### Air Brilliant

Decorative and diffuse distribution options to set the mood and ambience.

#### LED OPTIONS

Available in a range of white options (2200K-5700K CCT), Tunable White, or RGBW. Also available in 17 colours.



Air Brilliant range available in various distributions for decorative and ambient effect.

DISTRIBUTION	DESCRIPTION
Air Diamond	Cut glass with high refractive effect producing a distinct star-shaped pattern and bright centre point
Air Prism	Cut glass with a soft yet defined kaleidoscope effect
Air Wand	Modern festoon dual lighting effect
Air Globe	Modern festoon lantern. Choose from Globe Closed, Globe Open, Globe Half, Globe Silver, Globe Frosted or Globe Glass.



White WT Cool					White <b>WT</b> Neutral	White <b>WT</b> Warm	PhotoR ed <b>HR</b> 650-670n m
Violet VL 400-420n m	RoyalB lue <b>RY</b> 450-460n m	Blue <b>BL</b> 460-475n m	Cyan <b>CY</b> 490-510n m	Green <b>GR</b> 520-535n m	Amber AM 585-595n m	Red-Orange RO 610-620n m	Red <b>RD</b> 620-630n m
		Phosphor PB Blue	Phosphor PC Cyan	Phosphor PL Lime	Phosphor PA Amber	Phosphor PO Red-Orange	Phosphor PR Red
	·			Phosphor PM Mint	Phosphor PY Yellow		









#### ACCESSORIES, FINISHES & **EXTRA OPTIONS**

Choose your finish, accessories and any additional options. LED Puck Air Catenary comes standard in anodised black marine grade aluminium with matching lens ring.

Please note: Air Batwings, Air Floods and Air Street distributions are **not compatible** with Air accessories



Pole mounting options also available

## New Air Projector Accessory!

Pair Air Pendant with our economical wall and pole mounting option, Air Projector.

FINISH / ACCESSORY		DESCRIPTION
Black Matte Body (Standard)		Anodised standard black marine grade aluminium
Black Lens Ring Finish (Standard)		Standard black lens ring finish
Gold Lens Ring Finish		Gold lens ring finish
Silver Lens Ring Finish		Silver lens ring finish
Painted Finish		Painted finish (please specify or contact us)
CRI 90+		CRI90+
Barn Doors		4 door adjustable barn doors
Air Lens Cover	0	Polycarbonate lens cover

Spec Your LED Puck Air The Way You Want It!









#### HARDWARE

Mounting hardware sets are available for various mounting surface types. Sets come complete with Mount, Turnbuckles, blocks and grub screws. Cable and Drivers are available separately. See our Mounting Reference Guide for more details or contact your supplier.

#### Total Installed horizontal loading:

40-50kg tensile force.





Masonry Mount Set

For masonry surfaces



POLXXX-SET

Pole / Tree Mount Set

\*Remember to specify diameter. For example, the code P150 means one Pole/ tree Mount Set to fit 150mm diameter.







Universal Plate Mount Set Please contact us for advice.




For metal surfaces

Mounting hardware sets available for all surface types.

#### CONNECTION

Air Catenary has a combined all-in-one twin cable suspension and power system, including Dim over power. There is no need for a separate power cable.

Air will conveniently mount and connect simultaneously via its screw on/off cap making repositioning simple.



Luminaire connected (cap on) Side view

Luminaire disconnected (cap off) Isometric view.

Not to scale









<sup>\*</sup>Specifications are subject to change without notice.

#### SPECIFY YOUR AIR CATENARY

Customise your Planet LED Puck Air to meet your specific requirements. Refer to the sample product code and accompanying product code table provided for guidance. For more detailed information, visit our website or contact your Planet Lighting supplier.

#### AIR CATENARY DISTRIBUTION COLOUR OPTION(S) BODY AIR-CAT-ST-SN-30-9 GR: Gold lens ring SR: Silver lens ring 90: CRI90+ see more options 22: 2200K ST: Standard -27: 2700K AX: Axis SN: Snoot 30: 3000K PE: Pendant LS: Spot 35: 3500K LN: Narrow see more options LM: Medium LW: Wide

#### Ask Us

#### PRODUCT CODES

#### Body

ST	Standard body
AX	Axis body (pan and tilt)
PE	Pendant body

#### Distribution

#### Air Director Range

SN	Snoot	Beam Limiter
LS	Spot	Extra Narrow Spot
LN	Narrow	Narrow Spot
LM	Medium	Medium Spot
LW	Wide	Wide Spot
FN	Flood Narrow	Narrow Flood
FM	Flood Medium	Medium Flood
FW	Flood Wide	Wide Flood

LO	Oval	Wide Elliptical
BS	Square	Batwing Square
BL	Line	Batwing Line
ZO	Zoom	Adjustable Focus
IR	Iris	Adjustable Limiter

Air Street Range			
T1	T1		
T2	T2		
Т3	Т3		
T4	T4		

#### Air Brilliant Range

see more options

DI	Diamond
PR	Prism
WA	Wand
GO	Globe Open
GC	Globe Closed
GH	Globe Half
GS	Globe Silver
GF	Globe Frosted
GG	Globe Glass
	Custom Beam Angle (please enquire)

#### Colour

22	2200K
27	2700K
30	3000K
35	3500K
40	4000K
50	5000K
57	5700K

VT	Violet
RY	Royal Blue
BL	Blue
РВ	PC Blue
CY	Cyan
PC	PC Cyan
GR	Green
PM	PC Mint
PL	PC Lime
PY	PC Yellow

AM	Amber	
PA	PC Amber	
PO	PC Red-Orange	
RO	Red-Orange	
PR	PC Red	
RD	Red	
PH	Photo Red	
RGBW	RGBW	
TW	Tunable White	
Custom (please enquire)		

#### **Custom Options**

GR	Gold Lens Ring Finish
SR	Silver Lens Ring Finish
Р	Painted Finish (please specify)
90	CRI 90+
BD	Barn Doors
LC	Air Lens Cover

\*Specifications are subject to change without notice.







